



General specifications	
Product name	IKEPE Disjoncteur 20A Ph+N courbe C 4.5kA 230V
Part no.	DISJPNC20
EAN	3700609632936
Product Length/Depth	86 millimetre
Product height	73 millimetre
Product width	17.5 millimetre
Product weight	0.13 kilogram
Compliances	RoHS conform

Delivery program

Application	xPole - Switchgear for residential and commercial applications Switchgear for residential and commercial applications
Number of poles	Single-pole + N
Number of poles (total)	2
Number of poles (protected)	1
Tripping characteristic	C
Release characteristic	C
Amperage Rating	20 A
Type	PLG4 Miniature circuit breaker

Technical Data - Electrical

Voltage type	AC
Rated operational voltage (Ue) - max	230 V
Rated insulation voltage (Ui)	440 V
Rated impulse withstand voltage (Uimp)	4 kV
Frequency rating - min	50 Hz
Frequency rating - max	60 Hz
Rated switching capacity (IEC/EN 60898-1)	4.5 kA
Rated short-circuit breaking capacity (EN 60898) at 230 V	4.5 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V	4.5 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V	0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V	0 kA
Overvoltage category	III
Pollution degree	2

Technical Data - Mechanical

Width in number of modular spacings	1
Built-in depth	70.5 mm
Degree of protection	IP20
Connectable conductor cross section (solid-core) - min	1 mm ²
Connectable conductor cross section (solid-core) - max	25 mm ²
Connectable conductor cross section (multi-wired) - min	1 mm ²
Connectable conductor cross section (multi-wired) - max	25 mm ²

Design verification as per IEC/EN 61439 - technical data

Rated operational current for specified heat dissipation (In)	20 A
Heat dissipation per pole, current-dependent	0 W
Equipment heat dissipation, current-dependent	3.7 W

Static heat dissipation, non-current-dependent		0 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		75 °C
Additional information		
Current limiting class		3
Features		Concurrently switching N-neutral Additional equipment possible
Special features		Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
Used with		Miniature circuit breaker PLG4

Technical data ETIM 9.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)		
Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecl@ss13-27-14-19-01 [AAB905019])		
Built-in depth	mm	70.5
Release characteristic		C
Number of poles (total)		2
Number of protected poles		1
Rated current	A	20
Rated voltage	V	230
Rated insulation voltage Ui	V	440
Rated impulse withstand voltage Uimp	kV	4
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	kA	4.5
Voltage type		AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	kA	4.5
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	0
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	0
Frequency	Hz	50 - 60
Power loss	W	4.9
Current limiting class		3
Flush-mounted installation		No
Concurrently switching neutral conductor		Yes
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		1
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 75
Connectable conductor cross section multi-wired	mm ²	1 - 25
Connectable conductor cross section solid-core	mm ²	1 - 25
Explosion-proof		No