



### General specifications

Product name			IKEPE Contacteur Jour / Nuit 20A 2F/NO monophasé
Part no.			CTJ/N20A
EAN			3700609642836
Product Length/Depth			80 millimetre
Product height			70 millimetre
Product width			17.5 millimetre
Product weight			0.136 kilogram
Compliances			RoHS conform

### Technical data ETIM 9.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652)			
Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board (ecl@ss13-27-14-23-09 [AFZ821019])			
Function			Mechanical
Mounting method			DIN rail
Width in number of modular spacings			1
Built-in depth		mm	60
Number of contacts as normally open contact			2
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Control voltage 1		V	230 - 230
Type of control voltage 1			AC
Frequency control voltage 1		Hz	50 - 50
Control voltage 2		V	0 - 0
Type of control voltage 2			AC/DC
Frequency control voltage 2		Hz	0 - 0
Rated current		A	20
Supply voltage		V	250 - 250
Voltage type (supply voltage)			AC
Max. incandescent lamp load		W	0
Max. load fluorescent lamp		VA	0
Max. load fluorescent lamp (Duo circuit)		VA	0
Max. load fluorescent lamp (parallel compensated)		VA	0
Max. switching current (cos phi = 0.6)		A	0